

00000000000000000000000000000000

APPLICANT: Yukio Michishita

DOCKET NO.: 00USFP606

**LIGHT BRANCHING APPARATUS
AND OPTICAL COMMUNICATION SYSTEM USING THE SAME**

Background of the Invention

5 1. Field of the Invention

 The present invention relates to a light
branching apparatus used in an optical fiber
communication system, and more particularly, to a
light branching apparatus used in an optical fiber
10 communication system for transmitting optical signal
with different wavelengths.

2. Description of the Related Art

 As the increase of signals to be transmitted,
an optical fiber communication system using an optical
15 fiber has been widely used. The index of refraction
of the optical fiber, e.g., the optical fiber formed
of quartz glass used in such an optical fiber
communication system becomes smaller when the
wavelength of light becomes longer. With the optical
20 finer of quartz glass, when the wavelength becomes
longer, the propagation speed becomes faster. On
contrary, when the wavelength becomes shorter, the
propagation speed becomes slower. This is called
positive wavelength dispersion.

25 Because of the presence of dispersion
characteristic, when a light pulse with a degree of
width in wavelength is inputted to the optical fiber,

09802985-034201

the output light pulse has a wider pulse width. As a result, degradation of transmission quality such as waveform distortion is caused. Especially, the influence is large when the transmission distance such as an under-marine transmission line is long. Also, the influence due to the degradation of transmission quality is remarkable when the transmission bit rate is increased. For example, when the bit rate is 10 Gps (giga bits per second), the time width of one slot is 1/10 Gps or 100 ps. Therefore, it is necessary to reduce the waveform distortion to a value as small as 1/10 or lower than 10 ps. For the purpose, the use of a dispersion compensation type optical fiber is conventionally proposed. In a system disclosed in Japanese Laid Open Patent Application (JP-A-Heisei 9-36814), an optical signal is propagated reciprocally between an erbium-doped optical fiber and the dispersion compensation type optical fiber to compensate both wavelength dispersion and propagation loss.

However, in the conventional optical fiber communication system, specific considerations are not paid to the branch of an optical signal from a main path to a branch path or synthesis of an optical signal from the branch path to the main path, when a light branching path is provided for a part of the transmission path. That is, when the branch path is

provided at the part of the transmission path, the length of the transmission path is different between the main path and the branch path. In this case, the effect of the branch compensation is not sufficient.

5 Fig. 1 is a diagram showing an optical fiber communication system in which a light branching apparatus is arranged and the wavelength dispersion on the transmission path can be compensated, as a system in which the above problem can be solved. In the

10 optical fiber communication system disclosed in Japanese Laid Open Patent Application (JP-A-Heisei 9-153859), a light branching apparatus 13 is interposed between a light transmitter station 11 and a light receiver station 12. An optical signal branched by

15 the light branching apparatus 13 arrives at a light transmitter/receiver station 14. The light transmitter/receiver station 14 outputs the received optical signal as an output signal 15, and receives an optical transmission signal 16 from an apparatus (not

20 shown) to transfer to the light receiver station 12 via the light branching apparatus 13.

Fig. 2 is a diagram showing the structure of a conventional light branching apparatus. The light branching apparatus 13 is composed of an optical

25 switch 13A and a light separating/synthesizing unit 13B. In general, the light branching apparatus 13 operates to relay communication between the light

09802985-034004

transmitter station 11 and the light receiver station 12, between the light transmitter station 11 and the light transmitter/receiver station 14, and between the light transmitter/receiver station 14 and the light receiver station 12. If any fault occurs on the transmission path between the light branching apparatus 13 and the light receiver station 12 as shown by the symbol x, the optical switch 13A switches the transmission path to a standby side as shown by the arrow 13C to ensure communication between the light branching apparatus 13 and the light receiver station 12.

In the conventional optical fiber communication system, as shown in Fig. 1, it is supposed that a point distanced from a point A by one equalization interval in a direction of the light receiver station 12 via the light branching apparatus 13 is set to the point B, the distance from the light transmitter station 11 to the point A is set as n equalization intervals (n is an integer greater than zero), and the distance from the point B to the light receiver station 12 is set as m equalization intervals (m is an integer greater than zero). With one equalization interval of the main path, an equalizing fiber 18 is inserted on the input side of the light branching apparatus 13 to compensate 0.5 times of summed wavelength dispersion expected in the one

equalization interval, and an equalizing fiber 19 is inserted on the output side of the light branching apparatus 13 to compensate 0.5 times of summed wavelength dispersion expected in the one equalization interval. In this way, the optical signal is transmitted on the main path from the light transmitter station 11 to the light receiver station 12 while the summed wavelength dispersion for one equalization interval is compensated by the equalizing fibers 18 and 19 during the one equalization interval including the light branching apparatus 13.

Also, supposing that the distance from the point A on the main path to the point C on a branch path is one equalization interval, an equalizing fiber 21 is inserted on the output stage of the light branching apparatus 13 to compensate 0.5 times of summed wavelength dispersion expected in the one equalization interval. Supposing that the distance from the point D on an upstream path of the branch path to the point B on the main path is one equalization interval, an equalizing fiber 22 is inserted on the input stage of the light branching apparatus 13 to compensate 0.5 times of summed wavelength dispersion expected in the one equalization interval.

Accordingly, in the optical fiber communication system, the accumulated wavelength

The optical fiber communication system shown in Fig. 1 has the dispersion equalizing fibers 18, 19, 21, and 22 arranged to sandwich the light branching apparatus 13. The dispersion equalizing fibers 18, 19, 21, and 22 are optical fibers having characteristics

The optical fiber communication system shown in Fig. 1 has the dispersion equalizing fibers 18, 19, 21, and 22 arranged to sandwich the light branching apparatus 13. The dispersion equalizing fibers 18, 19, 21, and 22 are optical fibers having characteristics

for compensation of the wavelength dispersion, and the characteristic is adjusted based on the length of the fiber. Accordingly, the amount of dispersion in the system is predetermined. When the transmission path
5 length is changed, its resultant wavelength dispersion is also changed. Thus, transmission path length is different based on the length of each of the equalizing fibers 18, 19, 21, and 22.

Also, in order to prevent unbalance in the
10 length, the equalizing fibers 18, 19, 21, and 22 are arranged to sandwich the light branching apparatus 13 and to have compensation amount by 0.5 times in order. In this way, the number of fibers to be prepared are many such as the equalizing fibers 18, 19, 21, and 22,
15 their installation at the site may be a troublesome, time-consuming task as well as the number of overall components is increased.

Summary of the Invention

20 Therefore, an object of the present invention is to provide a light branching apparatus which requires no specific work for compensating wavelength dispersion when being installed at a part of a transmission path, and an optical communication system
25 using the same.

In an aspect of the present invention, a light branching apparatus includes an optical splitter

and a first wavelength dispersion compensator. The optical splitter splits an optical signal for a plurality of channels on a first optical fiber into at least a first optical channel signal on a first
5 channel of a second optical fiber and a plurality of second optical channel signals on a plurality of second channels of a third optical fiber. The first wavelength dispersion compensator is provided for the first channel and compensates wavelength dispersion of
10 the first optical channel signal due to the optical splitter.

Here, the light branching apparatus may further include a second wavelength dispersion compensator which is provided for the plurality of
15 second channels and compensates wavelength dispersion of the plurality of second optical channel signals due to the optical splitter.

Also, the first wavelength dispersion compensator may compensates wavelength dispersion of
20 the first optical channel signal due to the second optical fiber, in addition to the wavelength dispersion of the first optical channel signal due to the optical splitter. In this case, the first wavelength dispersion compensator may compensates the
25 wavelength dispersion of the first optical channel signal due to the second optical fiber by difference in length between the second optical fiber and the

Also, the light branching apparatus may further include the third wavelength dispersion compensator which is provided for the first channel and compensates wavelength dispersion of the first optical channel signal due to the second optical fiber.

Also, the light branching apparatus may further include the fourth wavelength dispersion compensator which is provided for a third channel of the second optical fiber and compensates wavelength dispersion of a third optical channel signal inputted to the light branching apparatus due to the second optical fiber.

Also, when the plurality of optical channel signals are compensated in units of channels, the first wavelength dispersion compensator may include at least a first wavelength dispersion compensating element for the channel of the first optical channel signal.

In another aspect of the present invention,
25 an optical communication system includes a first
optical fiber connected to a first station, a second
optical fiber connected to a second station, a third

optical fiber connected to a third station, and a light branching apparatus. The light branching apparatus includes an optical splitter and a first wavelength dispersion compensator. The optical
5 splitter splits an optical signal for a plurality of channels on a first optical fiber into at least a first optical channel signal on a first channel of a second optical fiber and a plurality of second optical channel signals on a plurality of second channels of a
10 third optical fiber. The first wavelength dispersion compensator is provided for the first channel and compensates wavelength dispersion of the first optical channel signal due to the optical splitter.

Here, the light branching apparatus may
15 further include a second wavelength dispersion compensator which is provided for the plurality of second channels and compensates wavelength dispersion of the plurality of second optical channel signals due to the optical splitter.

Also, the first wavelength dispersion
20 compensator may compensates wavelength dispersion of the first optical channel signal due to the second optical fiber, in addition to the wavelength dispersion of the first optical channel signal due to
25 the optical splitter. In this case, the first wavelength dispersion compensator may compensates the wavelength dispersion of the first optical channel

signal due to the second optical fiber by difference in length between the second optical fiber and the third optical fiber on which the first optical channel signal is selectively propagated. Also, the light
5 branching apparatus may further include an optical switch which switches a channel from one of the plurality of second channels to the first channel.

Also, the light branching apparatus may further include the third wavelength dispersion
10 compensator which is provided for the first channel and compensates wavelength dispersion of the first optical channel signal due to the second optical fiber.

Also, the light branching apparatus may further include the fourth wavelength dispersion
15 compensator which is provided for a third channel of the second optical fiber and compensates wavelength dispersion of a third optical channel signal inputted to the light branching apparatus due to the second optical fiber.

Also, when the plurality of optical channel
20 signals are compensated in units of channels, the first wavelength dispersion compensator may include at least a first wavelength dispersion compensating element for the channel of the first optical channel
25 signal.

In still another aspect of the present invention, a light branching apparatus includes an

optical switch and a wavelength dispersion compensator. The optical switch switches a transmission channel of a first optical channel signal on a first optical fiber from a first channel on a second optical fiber to a second channel on a third optical fiber. The wavelength dispersion compensator compensates wavelength dispersion of the first optical channel signal due to the second optical fiber by difference in length between the second optical fiber and the third optical fiber.

In yet still another aspect of the present invention, a light branching apparatus includes an optical splitter and a first wavelength dispersion compensator. The optical splitter splits at least a first optical channel signal from an optical signal for a plurality of channels on a first optical fiber to transmit onto a first channel of a second optical fiber. The first wavelength dispersion compensator is provided for the first channel and compensates wavelength dispersion of the first optical channel signal due to the second optical fiber. Also, the light branching apparatus may further include a second wavelength dispersion compensator which is provided for a second channel of the second optical fiber, and compensates wavelength dispersion of a second optical channel signal supplied on the second channel due to the second optical fiber.

the optical signal on the channel after the wavelength dispersion compensation;

Fig. 9 is a block diagram showing the structure of the optical fiber communication system using the light branching apparatus according to a second embodiment of the present invention; and

Fig. 10 is a block diagram showing the structure of the optical fiber communication system using the light branching apparatus according to a third embodiment of the present invention.

Description of the Preferred Embodiments

Hereinafter, a light branching apparatus of the present invention will be described below in detail with reference to the attached drawings.

Fig. 3 is a diagram schematically showing an optical fiber communication system using the light branching apparatus according to the first embodiment of the present invention. In the system of this embodiment, the light branching apparatus 103 is arranged in an intermediate location on a main transmission path between a light transmitter station 101 and a first light receiver station 102. An optical signal branched is received by a second light receiver station 104. A number of repeaters 107, each including an optical amplifier 106, are arranged in a predetermined interval between the light transmitter

station 101 and the light branching apparatus 103.
Provided on each transmission path 108 between the two
adjacent repeaters 107 are a dispersion shift fiber
(DSF) 111 and dispersion compensate fiber (DCF) 112
5 which has a characteristic opposite to that of the DSF
111 to compensate the wavelength dispersion. Also,
the arrangement is provided between the light
branching apparatus 103 and the first light receiver
station 102. Also, a combination of repeaters 107,
10 DSFs 111, and DCFs 112 (not shown) is arranged on the
transmission path between the light branching
apparatus 103 and the second light receiver station
104, when the transmission path is long to an extent.

The light branching apparatus 103 is composed
15 of a wavelength dispersion compensator 114 for the
main transmission path and another wavelength
dispersion compensator for a sub transmission path.
In this way, in the optical fiber communication system
of this embodiment, the light branching apparatus 103
20 is characterized by the two wavelength dispersion
compensators 114 and 115 provided therein. Therefore,
a worker is needed only to simply install the light
branching apparatus 103 in a desired position on the
transmission path.

25 Fig. 4 is a diagram schematically showing the
structure of the light branching apparatus of this
embodiment. The light branching apparatus 103 has

eight dispersion compensator circuits 122₁ to 122₈,
provided for first to eighth branch paths 123₁ to 123₈,
which are separated for every wavelength range of an
optical fiber 121. In this example, the dispersion
5 compensator circuits 122₁ to 122₄ correspond to the
dispersion compensator 114 and the dispersion
compensator circuits 122₅ to 122₈ correspond to the
dispersion compensator 114 in Fig. 3. The dispersion
compensator circuits 123₁ to 123₈ can compensate the
10 wavelength dispersion at once on all the wavelength
ranges to be transferred through the light branching
apparatus 103. Commercially available circuit
elements which are different in a compensation amount
but identical in the size can be used as the
15 dispersion compensator circuits 123₁ to 123₈.
Therefore, the dispersion compensator circuits 123₁ to
123₈ are selected and used to have the compensation
characteristic determined in accordance with the
dispersion amount determined based on the size or
20 other property of the light branching apparatus 103
using an optical signal of a predetermined wavelength
as a reference. In this embodiment, the branch paths
125₁ to 125₄ through the dispersion compensator
circuits 123₁ to 123₄ are connected on the main
25 transmission path to the first light receiver station
102, and the branch paths 125₅ to 125₈ through the
dispersion compensator circuits 123₅ to 123₈ are

connected on the sub transmission path to the second light receiver station 104.

Fig. 5 is a diagram showing a profile of the wavelength dispersion in two typical wavelengths in the optical fiber communication system of this embodiment. In the diagram, the horizontal axis represents the distance (km) from the light transmitter station 101 shown in Fig. 3 and the vertical axis represents the wavelength dispersion. The wavelength dispersion is not caused at the time when an optical signal is outputted from the light transmitter station 101, but the wavelength dispersion increases as the distance increases.

As shown in Fig. 5, the wavelength dispersion is compensated by the DCFs 112 and the wavelength dispersion compensators 114 and 115 not only in the light branching apparatus 103 but also on the transmission path 108. Fig. 5 shows the state in which the compensation is carried out to cancel the wavelength dispersion of the optical signal in a third channel 131, of a predetermined wavelength. In the figure, the wavelength dispersion is shown in a saw-tooth shape and the compensation is repeated. This is because the compensation by the DCFs 112 is carried out to the intervals of the transmission path. In this way, the compensation is carried out to each interval, compared with the conventional case where

the compensation is carried out once at the end of the transmission path. Therefore, the distortion of the waveform of the pulse optical signal can significantly be corrected in the waveform so that reproduction errors can be reduced.

Also, as shown in Fig. 5, the optical signal on a seventh channel 131, is sequentially compensated along the transmission path. In this case, the compensation by the DCFs 112 and the wavelength dispersion compensators 114 and 115 is carried out uniformly to all the wavelength ranges. As a result, the dispersion amount becomes gradually greater as the transmission distance increases.

Fig. 6 shows the state in which the compensation of the optical signal is carried out finally at the end station such as the first light receiver station 102 in the optical fiber communication system. As described above, the compensation of the wavelength dispersion of the optical signal is not carried out for every wavelength range between the light transmitter station 101 and the first 102 or second light receiver station 104 shown in Fig. 3. Therefore, the final dispersion compensation is carried out at both the first and second light receiver stations 102 and 104.

A characteristic curve 141 shown by the broken line in Fig. 6 represent the compensation in

the seven channel of an optical signal in a conventional light branching apparatus instead of the light branching apparatus 103 of this embodiment. In the first and second light receiver stations 102 and 5 104, the wavelength dispersion of the optical signal for every wavelength range is compensated before their reproduction. However, when the conventional light branching apparatus is used, the wavelength dispersion is excessively caused by dispersion by the 10 conventional light branching apparatus, compared with when the light branching apparatus 103 of the embodiment is used. For this reason, in this example, the compensation for an amount shown by S in the figure is short at the second light receiver station 15 104. On the contrary, in case of the optical signal 131, on the seventh channel shown by the solid line in this embodiment, the compensation is completely and fully carried out to the entire wavelength ranges in the second light receiver station 104 regardless of 20 whether the light branching apparatus 103 is arranged.

Fig. 7 shows the waveform of each of optical signals on channels before the dispersion compensation, while Fig. 8 shows the waveform of the optical signal on the channel after the dispersion compensation. As 25 shown in Fig. 7, the waveform of the optical signal 131, on the seventh channel is distorted by wavelength dispersion. As shown in Fig. 8, the waveform of the

optical signal 131, on the seventh channel is compensated by the light branching apparatus 103. It is apparent that the optical signal 131, of the seventh channel is successfully compensated and can be reproduced without any error.

Fig. 9 shows the optical fiber communication system using the light branching apparatus according to the second embodiment of the present invention. In the optical fiber communication system, the light branching apparatus 204 is arranged at an intermediate location between an A station 201 and a B station 202. The A station 201 transmits the optical signals 206₁ to 206₈ having different wavelengths λ_1 to λ_8 for the first to eighth channels, respectively. The optical signal 206₇ having the wavelength λ_7 on the seventh channel is branched to a C station 203 by the light branching apparatus 204, while the remaining optical signals are transferred to the B station 202. The C station 203 transmits an optical signal 216, having the wavelength λ_7 on the seventh channel to the light branching apparatus 204. The light branching apparatus 204 combines the optical signal 216, transmitted from the C station 203 with the optical signals 206₁ to 206₆ and 206₈ transmitted from the A station 201 and transfers a combined signal to the B station 202.

In the optical fiber communication system of

according to the third embodiment of the present invention. The light branching apparatus 301 includes therein an optical switch 302, a set of optical splitter/combiner 303, and a set of wavelength
5 dispersion compensators 304. The optical switch 302 is provided to switch between a transmission path between the A station and the B station and a transmission path between the A station and the C station. The optical splitter/combiner 303 splits an
10 optical signal and combines optical signals on the transmission path between the station A or B and the station C. The wavelength dispersion compensators 304 are provided on transmission paths on which optical signals are transferred when a fault has occurred on
15 the transmission paths between the light branching apparatus 301 and the B station as shown by the symbol X and the optical switch 302 switches the transmission paths. The wavelength dispersion compensators 304 are provided in the light branching apparatus 301 to
20 compensate the wavelength dispersion due to the change of the transmission paths in the length when the transmission paths are switched due to the fault.

In the third embodiment, the wavelength dispersion compensators in the first or second
25 embodiment may be added.

It should be noted that the first to third embodiments may be combined or independently realized.

As set forth above, according to the invention, the light branching apparatus of the present invention includes the wavelength dispersion compensators built in the light branching apparatus to
5 compensate the wavelength dispersion due to the light branching apparatus. Therefore, even if the light branching apparatus is simply arranged at an intermediate location on the transmission path, there is no change in the wavelength dispersion of the
10 optical signal to be transmitted to one end station. As a result, it is not necessary to change a circuit section of the end station for compensating the wavelength dispersion so that the existing fabrications can be used.

15 Also, according to the present invention, the light branching apparatus of the present invention has a set of the wavelength dispersion compensators provided therein to compensate wavelength dispersion of the optical signal in a specific wavelength range
20 due to a portion of the external transmission path. Therefore, the wavelength dispersion of the whole transmission path can be compensated by simply arranging the light branching apparatus on the transmission path.

25 Further, according to the present invention, the light branching apparatus of the present invention has the wavelength dispersion compensator arranged to

compensate the wavelength dispersion due to the change of the transmission path in the length when the transmission path is switched by the optical switch in the light branching apparatus. Therefore, even when
5 the transmission path is switched, the compensation of the wavelength dispersion is not required to be carried out outside the light branching apparatus. As a result, the quality of the optical signal can be maintained even if the optical switch is operated on
10 any fault.

Also, according to the present invention, in the light branching apparatus of the present invention, the wavelength dispersion compensators are detachable. Therefore, the wavelength dispersion amount can be
15 freely adjusted in accordance with the length of the transmission path.

Further, according to the present invention, in the light branching apparatus, the wavelength dispersion compensators are provided for each branch
20 path. Therefore, the wavelength dispersion can be separately compensated for every branch path.